



### DCS-F4626

#### 6 MP FISHEYE 360° FULL HD OUTDOOR POE CAMERA

##### KEY FEATURES

- 1/1.8" Progressive Scan CMOS
- 6MP Resolution
- Unique De-warping Image
- Low bitrate, Excellent low-light performance
- 3D DNR, dWDR, ICR, HLC
- Smart IR Range 10m

##### DIMENSION



##### ACCESSORIES



SN-CBK636 SN-CBK637 SN-CBK633



SN-CBK627B SN-CBK626

##### SPECIFICATIONS

CAMERA	
Image Sensor	1/1.8" Progressive Scan CMOS
Min. illumination	Color 0.01Lux(AGC ON);IR ON 0 Lux
Day & Night	ICR
Shutter Speed	1/5-1/50000
Auto Iris	N/A
Wide Dynamic Range	dWDR
Digital Noise Reduction	2D/3D
Lens	1.6mm
FOV	360 degrees
IR LED	6pcs
IR Range	10m
IMAGE	
Video Compression	H.264 High/Main/Baseline Profile, MJPEG
Bit Rate (CBR/VBR)	500kb-12000kb
Audio Compression	G.711, RAW_PCM
Max. Resolution	3072*2048@15fps
Stream	Stream1 3072*2048@15fps, 1920*1920/1440*1440/1920*1080@20fps Stream 2 1280*1280/720*720/D1@15fps/25fps/30fps
Image Setting	Rotate Mode, Saturation, Brightness, Contrast, Sharpness
De-warping	1F+3/5/7, 4PTZ, Fisheye, 180/360 degrees panorama
HLC	Yes
9:16 Corridor Mode	N/A
DIS	N/A
ROI	N/A
Defog	N/A
NETWORK	
Network Protocols:	IPv4, 802.1x, HTTP, HTTPS, TCP/IP, UDP/IP, RTSP, DHCP, NTP, RTCP/RTP, PPPoE, SMTP, DNS, UPnP, FTP, ICMP, IGMP, Unicast and Multicast
Alarm Trigger	Motion detection, Network disconnect, Disk alarm, I/O alarm
RTSP Video	Standard RFC2326, Support QuickTime / VLC Player.
Security	User security authentication, Reset, Hardware Watch Dog
Web Language	English, Chinese, Polish, Italian, Portuguese, Spanish
System Compatibility	Onvif
INTERFACE	
Ethernet	1 Ethernet (10/100 Base-T) RJ-45 Connector
Microphone	Yes (built-in)
Audio I/O	1ch Audio In, 1ch Audio Out
Alarm I/O	1ch Alarm In, 1ch Alarm Out
RS485	N/A
BNC Output	N/A
Reset Button	Yes
Edge Storage	Micro SD/SDHC/SDXC slot, Max 64GB
GENERAL	
Power Supply	AC24V/DC12V/POE
Power Consumption	5W IR LED OFF; 8W IR LED ON
Operating Temperature	Starting Temperature: -30 °C ~ 60 °C (-22 °F ~ 140 °F) Working Temperature: -40 °C ~ 60 °C (-40 °F ~ 140 °F)
Operating Humidity	0% - 90% RH
Ingress Protection	IP66
Approvals	CE / FCC
Product Dimensions	φ160*46.8mm
Product Weight	700g