

DCS-P4



PACKAGE CONTENTS:

- 1x 4CH H.265 2MP DVR (DVR-F2104-M2)
- 2x 2MP plastic dome indoor camera (DCS-F2612-L1P2)
- 2x 2MP plastic bullet outdoor camera (DCS-F2712-L1P2)
- 4x 18.5m BNC cable
- 1x HDMI cable
- 1x DC12V/2A Power adaptor for camera 1x 1 to 4 power supply Splitter



DCS-F2612-L1P2

2MP Fixed Dome AHD Camera



Key Features

- 1/2.9" CMOS Sensor
- AHD / TVI / CVI / CVBS video Output
- 2.8mm Fixed Lens
- Housing Material: Plastic
- Support 2D DNR

Camera	
Image Sensor	1/2.9" CMOS Sensor
Signal System	PAL/NTSC
Effective Pixels	1920(H) x 1080(V)
Electronic Shutter	AUTO/ 1/50 (1/60) -1/50,000sec
Min. Illumination	0.01Lux@(F1.2,AGC ON), 0LUX with IR
Video Frame Rate	PAL/NTSC: 25/30fps
Video Output	AHD / TVI / CVI / CVBS
Camera Features	
S/N Ratio	≥50dB
Noise Reduction	2D DNR
Day & Night	EXT/Auto/Color/B&W
AWB	Auto/Manual
WDR	D-WDR
LED	1pcs SMD LED
LED Range	20M
Lens	
Focal Length	2.8mm Fixed Lens
Angle of View	Horizontal: 105°
Lens Type	Fixed Iris
Mount Type	M12
General	
Housing Material	Plastic
Power Supply	DC12V(±10%)
Power Consumption	<5W
Working Temperature / Humidity	-20~+60°C RH95% MAX
Dimensions(W×D×H)	Φ84 x 70mm
Weight	90g



DCS-F2712-L1P2

2MP Fixed Bullet AHD Camera



Key Features

- 1/2.9" CMOS Sensor
- AHD / TVI / CVI / CVBS video output
- 3.6mm Fixed Lens
- Housing Material: Plastic
- Support 2D DNR

Camera	
Image Sensor	1/2.9" CMOS Sensor
Signal System	PAL/NTSC
Effective Pixels	1920(H) x 1080(V)
Electronic Shutter	AUTO/ 1/50 (1/60) -1/50,000sec
Min. Illumination	0.01Lux@(F1.2,AGC ON), 0LUX with IR
Video Frame Rate	PAL/NTSC: 25/30fps
Video Output	AHD / TVI / CVI / CVBS
Camera Features	
S/N Ratio	≥50dB
Noise Reduction	2D DNR
Day & Night	EXT/Auto/Color/B&W
AWB	Auto/Manual
WDR	D-WDR
LED	2pcs SMD LED
LED Range	20M
Lens	
Focal Length	3.6mm Fixed Lens
Angle of View	Horizontal: 78°
Lens Type	Fixed Iris
Mount Type	M12
General	
IP Rating	IP66
Housing Material	Plastic
Power Supply	DC12V(±10%)
Power Consumption	< 5W
Working Temperature / Humidity	-20~+60°C RH95% MAX
Dimensions(W×D×H)	55 x 55 x 154mm
Weight	130g




DVR-F2104-M2 4CH, 5MP Lite DVR

Key Features

- 4CH, 1SATAHDMI video output interface.
- Support AHD/TVI/CVI/CVBS/IP Cameras
- Support AHD/TVI cameras up to 5MP, CVI up to 4MP
- Support H.265+/H.265/H.264+/H.264
- Support Smart Playback & analytics
- Support 2 extra IP Ch
- Support video quality detection (VQD)

Specification	
VIDEO & AUDIO INPUT	
Video Input	4ch BNC interface (1.0Vp-p, 75 Ω)
TVI /AHD	5MP,4MP,1080P, 720P
CVI	4MP,1080P,720P
IPC	Up to 6ch 5MP
Audio Input	1-ch, RCA (2.0 Vp-p, 1 KΩ)
Two-way Talk	1-ch, multiplex with Audio Input (RCA)
VIDEO & AUDIO OUTPUT	
HDMI	1ch, resolution: 2k(2560x1440)/30Hz,1920x1080/60Hz,1280x1024/60Hz,1280x720/60Hz,1024x768/60Hz
VGA	1ch, resolution: 1920x1080/60Hz,1280x1024/60Hz,1280x720/60Hz,1024x768/60Hz
CVBS output Support	CVBS output Support
Audio Output 1-ch, RCA	Audio Output 1-ch, RCA (Linear, 1kΩ)
RECORDING	
Compression	Compression H.265/H.265+/H.264/H.264+
Resolution	4ch 5MP Lite@12fps; 4ch 4MP Lite/1080P@15fps; 1080P Lite@25fps 720P/960H/D1/CIF real time
Frame Rate(fps)	1fps-25fps (PAL) / 30fps (NTSC)
Video Bit Rate	11Kbps-4582Kbps
Record Mode	Manual, Schedule, Alarm
Audio Compression	G.711a
Audio Bit Rate	64Kbps
PLAYBACK & BACKUP	

Interfaces



Playback Mode	Smart Playback/Normal/Time Division/ Label/ Event/ Picture Playback
Playback Rate	4ch Playback
Backup Mode	USB Device/Network
SMART FUNCTION	
Smart Detection for Analog	4CH line crossing detection, area Intrusion,
Smart Playback for Analog	Line Crossing/Are Intrusion /Motion Detection
Online Upgrade	Supported
NETWORK	
Ethernet	1 RJ-45 10/100 Mbps self-adaptive Ethernet interface
Network Function	HTTPs, HTTP, TCP/IP, IPv4, UPnP, Onvif2.6, RTSP, RTCP, UDP, SMTP, SNMP, Multicast, IGMP, NTP, DHCP, DNS, DDNS, FTP, P2P
Smart Phone	IOS (iPhone, iPad), Android (Phone, Pad)
HARD DISK	
SATA	1 HDD
Capacity	Up to 10TB capacity for each HDD
EXTERNAL INTERFACE	
Serial Interface	NA
USB Interface	2 × USB
GENERAL	
Power Supply	DC12V, 1.5A
Power Consumption	≤10W (without HDD)
Working Environment	-10°C~+55°C / 10%~90%RH
Dimension (W×D×H)	250 x 230 x 45mm
Weight (without HDD)	1.5kg
Certification	CE, BIS
SYSTEM MANAGEMENT	
Mobile Software	D-Link Smart CCTV App
Desktop Software	DSVS (D-Link Smart Video Surveillance)
System Requirement for Web Interface	