

Product Highlights

Connect up to 16 PCs Manage several computers with one monitor, one keyboard and one mouse.

Switch between PCs quickly and easily Switch between computers quickly and easily using the buttons located on the front panel or IR remote controller.

Hot-plugging You don't need to turn your computers off before installing the device.



KVM-450 16-Port KVM Switch with VGA and USB Ports

Specifications

- VGA & USB connectors
- Up to 16 connected PCs
- Switching between PCs with the buttons located on the front panel or IR remote controller
- USB port for connecting external devices
- Hot-plugging
- Autoscan mode
- 19-inch rack mountable

The D-Link KVM-450 16-port KVM switch with VGA and USB ports allows you to manage up to sixteen computers with one monitor, one keyboard and one mouse. The KVM-450 requires no driver installation and can function without external power adapter connection by powering from USB port of your PC (the included power adapter can be used when connecting external device, for example, USB-disk, to the USB port of the KVM-450). This KVM switch supports hot-plugging - you don't need to turn your computers off before installing the device. The KVM-450 allows you to switch between computers quickly and easily using the buttons located on the front panel or IR remote controller. The KVM-450 supports autoscan mode, which provides automatic switching to the next PC after the scan interval expires. This KVM switch can be mounted in a 19-inch rack with the included mounting brackets.



KVM-450 16-Port KVM Switch with VGA and USB Ports

Technical Specifications		
Hardware		
Ports for connecting KVM cables	16 VGA ports	
Ports for connecting management console	 Monitor (local): VGA Keyboard (local): USB Type-A Mouse (local): USB Type-A 	
Port for connecting external devices	• USB Type-A	
KVM cable connectors for connecting PC	 Video: 15-pin HDB connector (VGA) Keyboard/Mouse: USB Type-A connector 	
LEDs	16 port LEDs for connected PCs	
Buttons	16 port switching buttonsReset button	
Enclosure	Metal, 19-inch rack mountable	
General Specifications		
Connected PCs	* Up to 16	
Autoscan mode	• Yes	
Switching between PCs	 Switching buttons on the front panel IR remote controller 	
Sound notification of switching	• Yes	
Max. resolution	• 1920x1440	
Physical Parameters		
Dimensions (L x W x H)	* 490 x 180 x 50 mm	
Weight	* 2.91 kg	
Environmental Conditions		
Power Supply	 From USB port on PC Power adapter when using external devices 	
Temperature	 Operating: -50 to 80 °C Storage: -20 to 60 °C 	
Humidity	* 0% to 80% non-condensing	



KVM-450 16-Port KVM Switch with VGA and USB Ports

Order Information	
Part Number	Description
KVM-450/C	16-Port KVM Switch with VGA and USB Ports
Optional Accessories*	
DKVM-CU/B	1.8 m KVM Cable with VGA and USB
DKVM-CU3/B	3 m KVM Cable with VGA and USB
DKVM-CU5/B	5 m KVM Cable with VGA and USB
* NOTE! The KVM cables of hardware revision B are compatible only with the KVM-450 KVM switch of hardware revision C.	



Specifications are subject to change without notice. D-Link is a registered trademark of D-Link Corporation and its overseas subsidiaries. All other trademarks belong to their respective owners. ©2019 D-Link Corporation. All rights reserved.