

### Product Highlights

#### Connect up to 4 PCs

Manage several computers with one monitor, one keyboard and one mouse.

#### Switch between PCs quickly and easily

Switch between computers quickly and easily using the buttons located on the top panel or keyboard hot keys.

#### Hot-plugging

You don't need to turn your computers off before installing the device.



## DKVM-4U 4-Port USB KVM Switch

### Specifications

- VGA & USB connectors
- Up to 4 connected PCs
- Switching between PCs with the buttons located on the top panel or keyboard hot keys
- Hot-plugging
- Autoscan mode

The D-Link DKVM-4U 4-port USB KVM switch allows you to manage up to four computers with one monitor, one keyboard and one mouse. The DKVM-4U requires no driver installation and no external power adapter connection. This KVM switch supports hot-plugging - you don't need to turn your computers off before installing the device. The DKVM-4U allows you to switch between computers quickly and easily using the buttons located on the top panel or keyboard hot keys. The DKVM-4U supports autoscan mode, which provides automatic switching to the next PC after the scan interval expires.

Technical Specifications	
<b>Hardware</b>	
Ports for connecting KVM cables	• 4 VGA ports
Ports for connecting management console	• Monitor (local): VGA • Keyboard (local): USB Type-A • Mouse (local): USB Type-A
Port for connecting USB-disk	• USB Type-A
KVM cable connectors for connecting PC	• Video: 15-pin HDB connector (VGA) • Keyboard/Mouse: USB Type-A connector
LEDs	• 4 port LEDs for connected PCs
Buttons	• 4 port switching buttons
Enclosure	• Plastic
<b>General Specifications</b>	
Connected PCs	• Up to 4
Autoscan mode	• Yes
Switching between PCs	• Switching buttons on the top panel • Hot keys
Sound notification of switching	• Yes
Max. resolution	• 2048x1536
<b>Physical Parameters</b>	
Dimensions (L x W x H)	• 100 x 65 x 27 mm
Weight	• 725 g
<b>Environmental Conditions</b>	
Power Supply	• From USB port on PC (no external power adapter required)
Temperature	• Operating: 0 to 50 °C • Storage: -20 to 60 °C
Humidity	• 0% to 80% non-condensing
<b>Order Information</b>	
<i>Part Number</i>	<i>Description</i>
DKVM-4U/C	4-Port USB KVM Switch
<b>Optional Accessories*</b>	
DKVM-CU/B	1.8 m KVM Cable with VGA and USB
DKVM-CU3/B	3 m KVM Cable with VGA and USB
DKVM-CU5/B	5 m KVM Cable with VGA and USB
* <b>NOTE! The KVM cables of hardware version B are compatible only with the DKVM-4U KVM switch of hardware version C.</b>	