



## Model: DKVM-IP8 Console Management at Anywhere & Anytime

DKVM-IP8 defines a new class of remote KVM access device; it combines digital remote KVM access via IP networks with comprehensive and integrated system management.

DKVM-IP8 owes a convenient, remote KVM access and control via LAN or Internet. It captures, digitizes, and compresses video and transmits it with keyboard and mouse signals to and from a remote computer. Also it provides a non-intrusive solution for remote access and control. Remote access and control software runs on its embedded processors only but not on mission-critical servers, so that there is no interference with server operation or impact on network performance.


### ※ Features

- Manage multiple serves around the world.
- Built in 8 ports KVM.
- KVM access over IP, ISDN or analogous telephone line.
- BIOS level access.
- Virtual Storage Mapping.
- SSL encryption.
- No impact on server or network performance.
- Automatically senses video resolution for best possible screen capture.
- High-performance mouse tracking and synchronization.

### ※ Package contents

- DKVM-IP8\*1
- QIG (Quick Installation Guide)
- User Manual on CD-ROM\*1
- Cables:
  - ✓ 1-to-3 console cable (1.8M)\*2
  - ✓ Daisy-chain cable (0.9M)\*1
  - ✓ LAN Cable\*1
  - ✓ USB Cable (A-B)\*1
  - ✓ Null modem cable\*1
- Power Adapter\*1 (5V, 2.5A)
- Rack Mount Kit\*1

### ※ Diagram



### ※ Specification

Specification		DKVM-IP8	
PC Connection	Direct	8	
	Max. via Daisy Chain	120 (8 port + 16 port * 7 levels)	
Port Selection		Push button, Hotkey, OSD	
Connectors	Console	Keyboard	1*Mini Din 6 Female (Purple)
		Video	1*HDB15 Female (Blue)
		Mouse	1*Mini Din 6 Female (Green)
	Computer		8*SPHD 15 pin Female (Blue)
	Daisy Chain	Keyboard	1*Mini Din 6 Female (Purple)
		Video	1*HDB15 Female (Blue)
		Mouse	1*Mini Din 6 Female (Green)
	Serial Port		1*DB9 pin Male
	USB Port		1*USB 2.0 Type B
LAN		1*RJ-45 Female	
Power		1*DC Jack (Black)	
Emulation	Keyboard / Mouse	PS/2	
LED	Online	8	
	10 / 100 Mbps	1 (Orange / Green)	
	7-Segment	1	
Scan Intervals		5~99 Sec	
Reset button		1	
VGA Resolution		● Local: 1600*1200 ● Remote: 1280*1024	
Environment	Operation Temperature	0 ~ 5°C	
	Storage Temperature	-20 ~ 60°C	
	Humidity	0 ~ 80%, Non-Condensing	
Power Adapter		DC 5V, 2.5A	
Physical Properties	Housing	Metal	
	Weight	2,600g	
	Dimensions (L*W*H), mm	44*430*220	