

Dual-Band IP Phone with Belt Clip

DPH-200SE is a portable IP phone designed for office and home. It supports wireless connection and can realize fast roaming across APs, which is very suitable for those who need to walk around the office areas. With a belt clip, DPH-200SE is easy to use and can free your hands for other tasks.

DPH-200SE

- 1.8" TFT color display with backlight
- 2 SIP accounts
- HD Voice quality
- 2.4GHz & 5GHz Wi-Fi
- Built-in 4000mA battery
- 1 x Micro USB port
- 1 x 3.5mm headphone jack



Easy to Use, Flexible Deployment

DPH-200SE is equipped with a 1.8-inch TFT screen and user-friendly UI design.



Meet Various Application Needs

DPH-200SE is portable, and the belt clip can free your hands when it's inconvenient for you to hold the phone.



HD Voice Quality

DPH-200SE provides excellent voice quality for handset and hands-free scenarios.



High Security and compatibility

AES, SRTP and TLS call encryption ensures your conversations are secure.



Dual-Band Support

Supports built-in 2.4GHz & 5GHz Wi-Fi for easy deployment.



High-Capacity Battery

A powerful built-in 4000mA battery so you can move around while answering calls

Technical Specifications

General

Device Interface	1 x 3.5mm headphone jack 1 x Micro USB port
Buttons	6 features keys: hands-free speakerphone, voice mail, call, hang up, hold, mute 2 Soft Keys, 5 Navigate Keys, Volume+/-
Screen	1.8" 128 x 160px colour LCD screen with backlight, 16-bit depth of colour
Codec	Wideband: G.722, Opus, AMR-WB(Optional), G.711WB(Optional) Narrowband: G.711(A/u), iLBC, G.729A/B, G.723, G.726, AMR-NB(Optional)
DTMF	In-band, RFC 2833, SIP INFO
Call Features	Call hold, mute, DND, redial, auto answer, One-touch speed dial, hotline, SMS Call forward, call waiting, call transfer (Network dependent)
IP-PBX features	Anonymous call, anonymous call rejection, Voice mail, call park, call pickup, Message waiting indicator (MWI)

Network & Security

SIP	v1 (RFC2543), v2 (RFC3261) Proxy mode and peer-to-peer SIP link mode SDP (RFC2327), UDP/TCP
Time and date	Synchronization using SNTP
Security	NAT Traversal By STUN, SRTP, TLS, HTTPS certificate manager, AES encryption for configuration file
VPN	OpenVPN
Network	IPv4 /IPv6, Dual stack IPv4/IPv6 RTP/RTCP (RFC1889, RFC1890), ARP/RARP (RFC826/903), SNMPv2
Management Standards	TFTP/HTTP/HTTPS for Auto Provisioning, TR069 (TR104/TR106), RFC 1706, RFC2782, RFC2915, FACS, system log

Physical

Size	48 x 182 x 28mm
Weight	500g
Power input	Power adapter: DC 5V/2A \pm 5% Battery: 4000mA
Operating Temperature	0°C~45°C
Storage Temperature	-25°C~65°C

Certification

Regulation Compliance	CE & RoHS Compliant
-----------------------	---------------------

Order Information

Part Number	Description
DPH-200SE	Dual-Band IP Phone with Belt Clip