

Product Highlights

High-speed Internet

Latest VDSL2 standards provide Internet transmission speeds faster than ADSL for fast downloads and smooth streaming media

High-performance Wireless

Fast 802.11n wireless gives you superior speed and range while remaining compatible with older 802.11g/b devices

Safe Connection

Robust security features keep your connection secure and prevent unauthorized access to the network, keeping your data safe from prying eyes



DSL-G225 VDSL2 N300 4-port Wireless Router

Features

Superior Performance Wireless

- Integrated VDSL2 and ADSL2/2+
- 802.11n wireless LAN
- 4 Ethernet switch ports
- 2 external antennas
- WAN RJ-45 port

Robust Security Features

- WPA/WPA2 and WEP
- Stateful Packet Inspection (SPI)
- Firewall protection

High Speed Connectivity

- VDSL2 supports the latest transmission speeds
- WLAN with high-speed data transfer rates of up to 300 Mbps¹

Convenience Features

- User-friendly GUI for web configuration
- Quality of Service (QoS)
- Universal plug-and-play(UPnP)
- Print server
- Web filtering
- USB mass-storage

The DSL-G225 VDSL2 N300 4-port Wireless Router is everything you need for high-speed Internet access in your home. It combines a VDSL2 modem and high-end wireless router together to create a single, easy-to-use device that connects to the Internet, and shares that connection with all of your devices. Plug in a USB storage drive to effortlessly share your documents, video, photos, and music or connect to a printer.

Combination ADSL2+ Modem and Router

The DSL-G225 combines the functionality of a high-speed VDSL2 broadband modem and a wireless router in one device, meaning there is no need for separate modem and wireless router devices. Connect to your VDSL2 Internet Service Provider and share the Internet connection with both wireless and wired devices. Lastly, the DSL-G225 gives you the option to connect to your broadband modem using the WAN Ethernet port so you have the flexibility to access the Internet via DSL, Cable, or other connection types.

Fast and Reliable Home Network

With the VDSL2 N300 4-port Wireless Router, you can create a home network with high-speed wireless, for a reliable connection to wireless devices, and Fast Ethernet LAN ports for quick wired connection speeds. 802.11n wireless gives you the bandwidth to stream HD multimedia and feature-rich content across your home, so you can browse the Internet and stream digital media at combined speeds of up to 300 Mbps¹. Using Quality of Service (QoS) technology the DSL-G225 can be configured to give certain devices network priority over others so their Internet connection is always optimized.

USB Port for Additional Connectivity

The DSL-G225 features a built-in USB port to provide additional functionality for your network. Attach a printer or portable hard drive to share files with everyone, or even plug in a 3G USB modem to enjoy Internet connectivity in places without a wired Internet connection.



DSL-G225 VDSL2 N300 4-port Wireless Router

Easy to Set Up and Secure

Get the DSL-G225 up and running in no time using the intuitive web-based configuration utility. Simply connect the DSL-G225 to your computer, launch the configuration utility, and follow a few easy steps to get your home

network configured. You can also set up a secure network with the touch of a button using Wi-Fi Protected Setup (WPS). Simply press the WPS button to effortlessly establish a secure connection to a new device. Protect your network with WPA/WPA2 wireless encryption and a built-in NAT firewall, so you can shop online and do your online banking with confidence.



Technical Specifications General		
ADSL/ADSL2+ Standards	• T1.413i2, G.992.1 • G.dmt, G.992.2, G.lite • G.992.3 (G.bis/ADSL2)	• G.992.5 (ADSL2+) • Annex L (Reach Extended ADSL2)
VDSL Standards	 ITU-T G.993.2 Supports 8a, 8b, 8c, 8d, 12a, 12b, 17a profile US0 Annex A and Annex B band plans 	 PhyR Virtual noise Dying GASP Diagnostics mode
Functionality		
Protocol Features	 NAT/NAPT (RFC 1631) RIP v1 (RFC 1058) RIP v2 (RFC 1389) DNS AAL5 ARP DHCP Server/Client/Relay 	 IGMP Proxy IGMP Snooping PPPoA PPP0E MER IPv6 supported

DSL-G225 VDSL2 N300 4-port Wireless Router

Management Features	 QoS Traffic Prioritization/Classification Port-based priority 802.1 p (0~7) priority Diffserv-Codepoint IPQoS (TOS, 0~63) Source/Destination IP/port-based priority Application port-based priority User-defined priority (TCP/UDP/ICMP) 3 priority queues per PVC Traffic Shaping: PVC/VLAN port mapping (bridge mode) 	 Web-based GUI for remote/local management Embedded Web server Menu-driven Command Line Interface via Telnet, serial port or SSH Universal Plug and Play (UPnP) Internet Gateway Device (IGDv1.0) TR-69 	
Security Features	TCP/IP/Port/Interface Filtering MAC Filtering Day-time Parental Control	 URL Content Filtering (keyword filtering) Stateful Packet Inspection (SPI) Denial of Service prevention (DoS) 	
Wireless Features	 Standard: IEEE 802.11b/g/n Security: 64-bit, 128-bit WEP, AES, TKIP, WPA, WPA2, 802.11 	 Frequency range: 2.4 GHz to 2.484 GHz Antennas: 2 non-detachable dipole antennas 	
Status LEDs	Power DSL/WAN Internet LAN(1-4)	• WLAN • WPS • USB	
VPN	L2TP/PPTP/IPSEC VPN passthrough	L2TP/PPTP/IPSEC VPN passthrough	
Physical			
Dimensions (L x W x H)	• 182.3 x 127.5 x 26.1 mm (7.18 x 5.02 x 1.03 inches)		
Weight	• 274 g (9.67 ounces)		
Power	Supply: 12 V DC, 1 A		
Temperature	• Operating: 0 to 45 °C (32 to 113 °F)	• Storage: -20 to 70 °C (-4 to 158 °F)	
Humidity	Operating: 10% to 95% non-condensing	Storage: 5% to 95% non-condensing	
Certifications	• CE	• FCC	
Order Information			
Part Number	Description	Description	
DSL-G225	VDSL2 N300 4-port Wireless Router	VDSL2 N300 4-port Wireless Router	

¹ Maximum wireless signal rate derived from IEEE Standard 802.11a, 802.11b, 802.11g, and 802.11n specifications. Actual data throughput will vary. Network conditions and environmental factors, including volume of network traffic, building materials and construction, and network overhead, lower actual data throughput rate. Environmental conditions will adversely affect wireless signal range.

Updated 2016/01/20

