

USB-C to 2.5G Ethernet Adapter

Lightning-fast gigabit speeds without having to install a new network card.

DUB-E250

- 2.5G Ethernet Connectivity
- USB-C Connector
- Auto Speed Detection
- Supports Crossover Detection
- Supports Full-Duplex Mode
- Two LED indicators
- No power adapter required
- Bundled with a virtual CD for driver installation (for Windows)
- Backwards compatible (10/100/1000 Mbps)



**Up to 4600 Mbps
Full Duplex**



**2.5 Gigabit Ethernet
Connectivity**



**USB-C and Thunderbolt™
Support**

| General | |
|-------------------|--|
| Device Interfaces | RJ-45 Ethernet Port (10/100/1000/2500 Mbps), USB-C Connector |
| LED | Connection (orange), Link/ACT (flashing white) |

| Functionality | |
|--------------------|--|
| IEEE Standard | IEEE 802.3, IEEE 802.3u, IEEE 802.3ab |
| USB Specifications | USB 3.1 Gen 1, USB 3.0, USB 2.0 |
| Supports | IEEE 802.1P (Layer 2 Priority Encoding) IEEE 802.1Q (VLAN tagging) IEEE 802.3az (Energy Efficient Ethernet) IEEE 802.3bz (2.5GBASE-T) IEEE 802.3x (Full Duplex flow control) |

| Software | |
|----------------------|--|
| Auto Speed Detection | 10/100/1000/2500 Mbps |
| Crossover Detection | Auto-MDI/MDI-X |
| Power Management | Power Saving Mode when Ethernet cable is unplugged |
| Hot Pluggable | Yes |
| System Requirements | Windows 7/8/10, Mac OS 10.6 or later |

| Physical | |
|----------------------------------|--|
| Operating Mode Power Consumption | 250 mA |
| Standby Mode Power Consumption | 60 mA |
| Cable Length | 160 mm (6.3 in) |
| Dimensions | 53 x 21.5 x 15 mm (2.1 x 0.8 x 0.6 in) |
| Weight | 28.5 g (1.0 oz) |
| Operating Temperature | 10 to 45 °C (50 to 113 °F) |
| Storage Temperature | 10 to 70 °C (14 to 158 °F) |
| Operating Humidity | 10% to 85% non-condensing |
| Storage Humidity | 5% to 90% non-condensing |
| Certifications | CE, FCC, IC |

