

2.4GHz Wireless LAN



802.11b Wireless LAN Access Point

The D-Link Air DWL-700AP Access Point is designed to give 2.4GHz wireless LAN users low-cost yet secure access to an IEEE 802.11b wireless Local Area Network (LAN). This Access Point combines industry standards with versatile functions like repeater mode, and enhanced IEEE 802.11i security features like WEP, TKIP, and AES to give you wireless LAN interoperability and functionality at an affordable price.

Wireless Access

The DWL-700AP Access Point connects the wireless LAN nodes (workstations, print servers, etc.) together via a 2.4GHz IEEE 802.11b wireless interface. It listens to all data traffic and maintains a dynamically updated MAC address database. When necessary, IP addresses are matched to MAC addresses and information is stored in the database as well. A 10/100Mbps Fast Ethernet port provides a bridge between a wireless network and wired network. The DWL-700AP converts data packets over a wired Ethernet LAN into radio signals to be used on the wireless network and vice versa.

Built-in Bridge & Repeater Functions

The DWL-700AP can be configured to operate in any one of the following modes: (1) as a wireless access point, (2) a wireless client or (3) a repeater. With these built-in functions, the DWL-700AP gives you the flexibility to configure the device to as an access point at home or the office with normal wireless operation range requirements, or as a repeater that connects 2 wireless networks together when the number of wireless users increases and spreads in a wider area.

Network Security

In the air, transmitted data can be easily intercepted if not well protected by a security scheme. The DWL-700AP provides the necessary security, using the enhanced 64/128-bit industry-standard WEP (Wired Equivalent Privacy) encryption protocol. It also provides IEEE 802.11i security features such as embedded AES/TKIP security engine (hardware supported).

Web-based & SNMP Configuration/Management

The DWL-700AP can be configured and managed by HTTP (web-based configuration) or SNMP (SNMP v.2 support) through built-in MIBs. DHCP client and server are supported.

Key Features

- 802.11b 2.4GHz industry standard with wide range of wireless LAN interoperability
- 11Mbps data transfer rates
- 10/100Mbps auto-sensing Fast Ethernet port to bridge wireless LAN to Ethernet-based network
- Built-in repeater function

- Embedded AES/TKIP security engine
- SNMP v2 support
- Client access control via MAC address
- Configuration by HTTP and SNMP
- Management features: SNMP, HTTP, DHCP Server & Client

DWL-700AP Technical Specifications

Standards

- IEEE 802.11b wireless LAN
- IEEE 802.3 10BASE-T Ethernet
- IEEE 802.3u 100BASE-TX Fast Ethernet

Wireless LAN to Ethernet Interface Through RJ-45 10/100Mbps Fast Ethernet port

5

Frequency Range

2.4GHz to 2.4835GHz

Modulation Techniques

Direct Sequence Spread Spectrum (DSSS)

Data Rates

- 11 Mbps
- 5.5 Mbps
- 2 Mbps
- 1 Mbps - Auto fall-back

Data Rate & Modulation Scheme

- 11Mbps: CCK
- 5.5Mbps: CCK
- 2Mbps: Barker - 1Mbps: Barker

Operating Channels

- North America (FCC): 11
- Canada (DOC): 11
- Europe (ETSI): 13

Antenna

Detachable 2dBi Gain antenna with reverse SMA connector

Receive Sensitivity

@<8% -82 dBm (typical)

Transmit Output Power

18dBm (typical)

Operating Range

- Indoors: up to 100 m (328 feet) *
- Outdoors: up to 300 m (984 feet) *
- * Environmental factors may adversely affect operating range

Operating Modes

- Access Point
- Wireless client
- Repeater

Security

Data encryption: 64-bit, 128-bit-bit WEP (Wired Equivalent Privacy)

Device Management

- Web-based through Internet Explorer v6 or later; Netscape Navigator v.6 or later; or other Java-enabled browsers

- DHCP Server and Client

Physical & Environmental

Power Input - DC 5V, 2.0A

- Uses external AC power adapter

Dimensions

142 (L) x 109 (W) x 31 (H) mm (5.6 x 4.3 x 1.2 inches)

Weight 200 grams (0.44 lb.)

Operating Temperature 0° to 55° C (32° to 149° F)

Storing Temperature - 20° to 75° C (4° to 167° F)

Humidity

Up to 95%, non-condensing

2.4GHz Wireless LAN

Emission

- FCC Class B - CE Class B
- CE Class D

Box Includes

- DWL-700AP Wireless Access Point
- User's Manual on CD
- Quick Installation Guide
- 1.8 m Cat. 5 Ethernet straight-through cable
- Power Adapter





Ordering Information

DWL-700AP

Please specify your order as follows:		
BDWL-700AP	US standard power adapter, North America frequency (USA packaging)	
TDWL-700AP	US standard power adapter, North America frequency (Taiwan packaging)	
DWL-700AP/ANA	US standard power adapter, North America frequency	
DWL-700AP/ENA	EU standard power adapter, North America frequency	
DWL-700AP/BEU	UK standard power adapter, EU frequency	
DWL-700AP/EEU	EU standard power adapter, EU frequency	
DWL-700AP/NEU	Australia standard power adapter, EU frequency	
DWL-700AP/CN	For use in China (China packaging)	

802.11b Wireless LANAccess Point

D-Link

Specifications subject to change without prior notice. D-Link is a registered trademark and D-Link is a trademark of D-Link Corporation/D-Link System Inc. All other trademarks belong to their proprietors.

Germany France Benelux Italy Iberia Sweden Norway Denmark Finland Singapore Australia Japan China India Egypt UAE Turkey Israel Chile Brasil South Africa Russia Taiwan

D-Link Corp.

U.S.A

Canada

Europe

TEL: 1-949-788-0805	FAX: 1-949-753-7033
TEL: 1-905-8295033	FAX: 1-905-8295095
TEL: 44-20-8731-5555	FAX: 44-20-8731-5511
TEL: 49-6196-77990	FAX: 49-6196-7799300
TEL: 33-1-30238688	FAX: 33-1-30238689
TEL: 31-10-2045740	FAX: 31-10-2045880
TEL: 39-2-2900-0676	FAX: 39-2-2900-1723
TEL: 34-93-4090770	FAX: 34-93-4910795
TEL: 46-(0)8564-61900	FAX: 46-(0)8564-61901
TEL: 47-22-309075	FAX: 47-22-309085
TEL: 45-43-969040	FAX: 45-43-424347
TEL: 358-9-2707-5080	FAX: 358-9-2707-5081
TEL: 65-6774-6233	FAX: 65-6774-6322
TEL: 61-2-8899-1800	FAX: 61-2-8899-1868
TEL: 81-3-5434-9678	FAX: 81-3-5434-9868
TEL: 86-10-8518-2533	FAX: 86-10-8518-2250
TEL: 91-22-652-6696	FAX: 91-22-652-8914
TEL: 202-62-44615	FAX: 202-62-44583
TEL: 971-4-3916480	FAX: 971-4-3908881
TEL: 90-212-335-2525	FAX: 90-212-335-2500
TEL: 972-9-9715700	FAX: 972-9-971-5601
TEL: 56-2-232-3185	FAX: 56-2-232-0923
TEL: 55-11-3094-2910	FAX: 55-11-3094-2921
TEL: 27(0)1266-52165	FAX: 27(0)1266-52186
TEL: 7-095-737-3389	FAX: 7-095-737-3390
TEL: 886-2-2910-2626	FAX: 886-2-2910-1515
TEL: 886-2-2916-1600	FAX: 886-2-2914-6299

