

Product Highlights

10 Gigabit Connectivity

High bandwidth uplinks eliminate network bottlenecks and provide low-latency connections for network servers and storage

High Performance

Get the speeds your network needs with up to 640 Gbps switching capacity and 480 Mpps forwarding rate

Reliability

The DXS-F3500-32S supports dual load sharing for AC/DC power, as well as Data Center Bridging to provide "lossless Ethernet" transmission quality



DXS-F3500-32S

High Port Density Data Center TOR Switch

Features

High availability & Flexibility

- Two AC/DC hot-swappable power modules for 1+1 redundancy and load sharing.
- Five hot-swappable fan trays provide N+1 cooling redundancy.
- Supports Virtual Switching Unit (VSU) by leveraging Multi-Chassis Trunking (MCT) to avoid a single point of failure. (Up to four devices functioning together as a single unit)
- Ethernet Ring Protection Switching (ERPS) / Ethernet Automatic Protection Switching (EAPS)

Lossless Ethernet via Data Center Bridging (DCB)

- IEEE 802.1Qbb Priority-based Flow Control (PFC)
- IEEE 802.1Qaz Enhanced Transmission Selection (ETS).
- IEEE 802.1Qau Congestion Notification (CN)

Traffic Monitoring & Bandwidth Control

- Port mirroring/Bandwidth Rate Limit Control
- Broadcast/Multicast/Unicast storm control
- Single Rate Three Color Marker (srTCM)
- Two Rate Three Color Marker (trTCM)

D-Link's new generation DXS-F3500-32S switch delivers versatile feature set, High density port count in 1U rack mount size; suitable for Data Center TOR or Enterprise & campus environments CORE/Aggregation requirements. The DXS-F3500-32S a non-blocking architecture design provides high-performance L2/L3/L4 switches feature wire-speed switching capacity 10/40 Gigabit Ethernet switching, routing at ultra-low latency. DXS-F3500-32S provides 4 x 100BASE-T ports, 24 x 1/10GbE SFP/SFP+ ports, 2 x 40G QSFP+ Ports in compact 1U rack size.

High Availability & Flexibility

The DXS-F3500-32S switch feature a modular fan and power supply design for a high availability architecture. The hot-swappable design means that fans and power supplies can be replaced without affecting switch operation. The Multi-Chassis Trunking enables multiple DXS-F3500-32S switch to be configure in a Virtual chassis and can provide non-stop layer-3 routing forwarding even in case of failure of any switch in the virtual chassis.

Lossless Ethernet

Data Center Bridging (DCB) is an essential set of enhancements to Ethernet for networking in data center environments. The DXS-F3500-32S switch support several core components of Data Center Bridging (DCB) such as IEEE 802.1Qbb, IEEE 802.1Qaz, and IEEE 802.1Qau. IEEE 802.1Qbb (Priority-based Flow Control) provides flow control on specific priority to ensure there is no data-loss during network congestion. IEEE 802.1Qaz (Enhanced Transmission Selection) manages the allocation of bandwidth amongst different traffic classes. IEEE 802.1Qau (Congestion Notification) provides congestion management for data flows within network domains to avoid congestion.

Technical Specifications	
General	DXS-F3500-32S
Interfaces	4 x 1000BASE-T ports, 24 x 1/10GbE SFP/SFP+ ports, 2 x 40G QSFP+ Ports
Hardware Version	A1
Media Interface Exchange	Auto or configurable MDI/MDIX
Console Port	RJ-45 and Mini USB console ports for out-of-band CLI management
Management Port	10/100/1000BASE-T RJ-45 Ethernet for out-of-band IP management
USB Port	A-Type Port
Performance	
Switching Capacity	640 Gbps
Max. Forwarding Rate	480 Mpps
Packet Buffer Memory	9M
MAC Address Table	128K
Physical	
Power input	Dual Redundant AC Power supplies (100 to 230 V AC) Dual Redundant DC Power supply 36V ~ 72V (Available on request)
Dimensions	442x404x44 mm (W x D x H) 1U
Operating Temperature	0° to 50° C
Storage Temperature	-20° to 70° C
Operating Humidity	10%-90% non-condensing
Storage Humidity	5%-95% non-condensing
Certifications	
Safety	RoHS
Software Features	
Virtual Switching Unit (VSU)	Multi-Chassis Trunking
VSU devices	Virtual Stacking/Clustering of up to 4 units
Layer 2 Features	<ul style="list-style-type: none"> • MAC Address Table • Up to 128K entries • Flow Control <ul style="list-style-type: none"> • 802.3x Flow Control when using full-duplex • Back Pressure when using half-duplex • HOL Blocking Prevention • Spanning Tree Protocol <ul style="list-style-type: none"> • 802.1D STP • 802.1w RSTP • 802.1s MSTP • Root Guard • Loop Guard • Jumbo Frame <ul style="list-style-type: none"> • Up to 9K • 802.3ad, 802.1AX Link Aggregation <ul style="list-style-type: none"> • Max. 32 groups per device, 32 ports per group • ERPS (Ethernet Ring Protection Switching) • Port mirroring <ul style="list-style-type: none"> • Supports one-to-one, many-to-one • Supports mirroring for Tx/Rx/both • Supports 4 mirroring groups • Flow mirroring <ul style="list-style-type: none"> • Supports mirroring for Rx • VLAN mirroring • L2 protocol tunneling • Loopback Detection (LBD)
L2 Multicast Features	<ul style="list-style-type: none"> • MLD Snooping <ul style="list-style-type: none"> • MLD v2/v3 snooping • Supports 256 groups • Supports 64 static MLD groups • PerVLAN MLD Snooping • MLD Snooping Querier • Host-based MLD Snooping Fast Leave • MLD Proxy Reporting • IGMP Snooping <ul style="list-style-type: none"> • IGMP v1/v2/v3 snooping • Supports 8K IGMP groups • Supports 64 static IGMP groups • PerVLAN IGMP Snooping • IGMP Snooping Querier • Host-based IGMP Snooping Fast Leave • PIM Snooping

Layer 3 Multicast	<ul style="list-style-type: none"> • IGMP v1/v2/v3 • IGMP/MLD Proxy <ul style="list-style-type: none"> • DVMRP v3 • PIM-SM/SM v6/SSM/SDM • Multicast Source Discovery Protocol (MSDP)
L3 Features	<ul style="list-style-type: none"> • ARP <ul style="list-style-type: none"> • 512 static ARP • Supports Gratuitous ARP • ARP Proxy • Loopback interface • UDP helper • IPv6 tunneling <ul style="list-style-type: none"> • Static • ISATAP • GRE • 6to4 • IPv6 Neighbor Discovery (ND) • IGMP Proxy Reporting • VRRP v2/v3 • IPv6 Tunneling <ul style="list-style-type: none"> • Static • ISATAP • GRE <ul style="list-style-type: none"> • 6to4 • IP Interface <ul style="list-style-type: none"> • Supports 256 interfaces
L3 Routing	<ul style="list-style-type: none"> • Static routing <ul style="list-style-type: none"> • IPv4: 16K • IPv6: 8K • Supports Route Redistribution • Supports secondary route • Supports hardware routing entries shared by IPv4/IPv6 <ul style="list-style-type: none"> • IPv4: 16K • IPv6: 8K • Supports hardware L3 forwarding entries shared by IPv4/ IPv6 <ul style="list-style-type: none"> • IPv6: 4K • IPv6: 2K • Default routing • Policy-based Route (PBR) • Null route • Bidirectional Forwarding Detection (BFD) <ul style="list-style-type: none"> • IPv4/IPv6 static route • RIP • VRRP • RIP <ul style="list-style-type: none"> • RIP v1/v2 • RIPng • Graceful Restart (GR) Helper for RIP • Route Redistribution <ul style="list-style-type: none"> • Default route • Static route • RIP • RIPng • Null route • OSPF <ul style="list-style-type: none"> • OSPF v2/v3 • OSPF Passive Interface • Stub/NS Graceful Restart (GR) Helper for OSPF • Route Preference <ul style="list-style-type: none"> • OSPF v2/v3 • Route Redistribution <ul style="list-style-type: none"> • OSPF v2/v3 • Bidirectional Forwarding Detection (BFD) <ul style="list-style-type: none"> • OSPF • BGP4+
VLAN	<ul style="list-style-type: none"> • 802.1Q • 802.1v • Double VLAN (Q-in-Q) <ul style="list-style-type: none"> • Port-based Q-in-Q • Selective Q-in-Q • Port-based VLAN • MAC-based VLAN • Subnet-based VLAN • Private VLAN • VLAN group <ul style="list-style-type: none"> • Max. 4K static VLAN groups • Max. 4094 VIDs • ISM VLAN (multicast VLAN) • Voice VLAN • Auto Surveillance VLAN • VLAN trunking • GVRP <ul style="list-style-type: none"> • Up to 227 dynamic VLANs

AAA	<ul style="list-style-type: none"> • 802.1X Authentication <ul style="list-style-type: none"> • Supports port-based access control • Supports host-based access control • Dynamic VLAN assignment • Identity-driven policy (VLAN/ACL/QoS) assignment • Web-based Access Control (WAC) <ul style="list-style-type: none"> • Supports port-based access control • Supports host-based access control • Dynamic VLAN Assignment • Identity-driven Policy (VLAN/ACL/QoS) Assignment <ul style="list-style-type: none"> • MAC-based Access Control (MAC) <ul style="list-style-type: none"> • Identity-driven policy assignment <ul style="list-style-type: none"> • QoS assignment • ACL assignment • Supports port-based access control • Supports host-based access control • Compound Authentication • RADIUS and TACACS+ authentication • Authentication Database Failover • Guest VLAN
Quality of Service (QoS)	<ul style="list-style-type: none"> • 802.1p Quality of Service (QoS) • 8 queues per port • Queue handling <ul style="list-style-type: none"> • Strict • Weighted Round Robin (WRR) • Strict + WRR • Round Robin (RR) • Weighted Deficit Round Robin (WDRR) • CoS (Class of Service) based on: <ul style="list-style-type: none"> • 802.1p Priority Queues • DSCP, Physical Port • IP address, IP Subnet, IP Protocol • MAC address • VLAN • IPv6 Traffic Class • IPv6 Flow Label • TCP/UDP port <ul style="list-style-type: none"> • Queue handling <ul style="list-style-type: none"> • Strict • Weighted Round Robin (WRR) • Strict + WRR • Deficit Round Robin (DRR) • Bandwidth rate limit control <ul style="list-style-type: none"> • Port-based (ingress/egress, min. granularity 64 Kb/s) • Flow-based (ingress/egress, min. granularity 64 Kb/s) • Per queue bandwidth control (min. granularity 64 Kb/s) • Support for following actions: <ul style="list-style-type: none"> • Remark 802.1p priority tag • Remark ToS/DSCP tag
Data Center Bridging (DCB)	<ul style="list-style-type: none"> • 802.1Qbb Priority-based Flow Control (PFC) • 802.1Qaz Enhanced Transmission Selection (ETS) <ul style="list-style-type: none"> • 802.1Qau Congestion Notification (CN)
Access Control List (ACL)	<ul style="list-style-type: none"> • ACL based on: <ul style="list-style-type: none"> • 802.1p priority • VLAN • MAC address • Ether Type • IP address • DSCP • Protocol type • TCP/UDP port number • IPv4/IPv6 traffic class • IPv4/IPv6 Flow Label <ul style="list-style-type: none"> • Max. ACL entries: <ul style="list-style-type: none"> • Ingress <ul style="list-style-type: none"> • IPv4: 2K • IPv6: 1K • Egress <ul style="list-style-type: none"> • IPv4: 2K • IPv6: 1K • 3K VLAN access map • Time-based ACL

<p>Security</p>	<ul style="list-style-type: none"> • Port Security • Supports up to 12K MAC addresses per port/system • Broadcast/multicast/unicast storm control • D-Link Safeguard Engine • DHCP server screening • IP-MAC-Port Binding • Dynamic ARP Inspection • IP Source Guard • DHCP Snooping • IPv6 Snooping • DHCPv6 Guard • IPv6 Route Advertisement (RA) Guard • IPv6 ND Inspection 	<ul style="list-style-type: none"> • ARP Spoofing Prevention • Max. 64 entries • Duplicate Address Detection (DAD) • L3 Control Packet Filtering • Traffic Segmentation • Source - destination port • SSL • Supports v1/v2/v3 • Supports IPv4/IPv6 access • SSH • Supports SSH v2 • Supports IPv4/IPv6 access • BPDU attack protection
<p>Management</p>	<ul style="list-style-type: none"> • Web-based GUI (HTTP, HTTPS) • CLI • Telnet server • Telnet client • TFTP client • FTP client • Secure FTP (SFTP) server • Traffic monitoring • SNMP • Supports v1/v2c/v3 • SNMP Trap • System log • DHCP client • DHCP server • DHCP Relay options 60, 61, 82 • Multiple images • Multiple configurations • Flash file system • DNS client 	<ul style="list-style-type: none"> • CPU monitoring • MTU setting • ICMP tools <ul style="list-style-type: none"> • Ping • Traceroute • LLDP & LLDP-MED • DNS Relay • SMTP • DHCP Auto Configuration • NTP • RCP (Remote Copy Protocol) • RMON v1/v2 • Trusted host • Password encryption • Debug command • Switch Resource Management (SRM) • Microsoft Network Load Balancing (NLB)
<p>Operations, Administration, and Maintenance (OAM)</p>	<ul style="list-style-type: none"> • Cable diagnostics • 802.3ah Ethernet link OAM • D-Link Unidirectional Link Detection (DULD) • Dying Gasp 	<ul style="list-style-type: none"> • 802.1ag Connectivity Fault Management (CFM) • Y.1731 OAM • Optical Transceiver Digital Diagnostic Monitoring (DDM)

Ordering Information	
DXS-F3500-32S	4 x 1000BASE-T ports, 24 x 1/10GbE SFP/SFP+ ports ports, 2 x 40G QSFP+ Ports Two AC modular power supplies and five fan modules with front-to-back airflow.
Optional SFP Transceivers	
DEM-310GT	1000BASE-LX, single-mode, 10 km
DEM-311GT	1000BASE-SX, multi-mode, 550 m
DEM-312GT2	1000BASE-SX, multi-mode, 2 km
DEM-314GT	1000BASE-LHX, single-mode, 50 km
DGS-712	1000BASE-TX Copper to SFP Transceiver
DEM-410T	10GBASE-T SFP+ Transceiver
Optional SFP+ Transceivers	
DEM-431XT	10GBASE-SR SFP+ Transceiver (without DDM), 33 m: OM1 MMF, 82 m: OM2 MMF, 300 m: OM3 MMF
DEM-431XT-DD	10GBASE-SR SFP+ Transceiver (with DDM), 33 m: OM1 MMF, 82 m: OM2 MMF, 300 m: OM3 MMF
DEM-432XT	10GBASE-LR SFP+ Transceiver (without DDM), 10 km
DEM-432XT-DD	10GBASE-LR SFP+ Transceiver (with DDM), 10 km
DEM-433XT	10GBASE-ER SFP+ Transceiver (without DDM), 40 km
DEM-433XT-DD	10GBASE-ER SFP+ Transceiver (with DDM), 40 km
DEM-434XT	10GBASE-ZR SFP+ Transceiver (without DDM), 80 km
DEM-436XT-BXD	10GBASE-LR BiDi SFP+ Transceiver (without DDM), Wavelength Tx 1330 nm, Rx: 1270 nm, 20 km
DEM-436XT-BXU	10GBASE-LR BiDi SFP+ Transceiver (without DDM), Wavelength Tx 1270 nm, Rx: 1330 nm, 20 km
Optional 40 Gbps QSFP+ Transceivers	
DEM-QX10Q-LR4	40GBASE-LR4 transceiver, single-mode, 10 km
DEM-QX01Q-SR4	40GBASE-SR4 transceiver, multi-mode, OM3: 100 m/OM4: 150 m
Optional 40 Gbps QSFP+ Direct attached cable	
DEM-CB100QXS	40G QSFP+ to QSFP+ 1m Direct attach cable
DEM-CB300QXS	40G QSFP+ to QSFP+ 3m Direct attach cable
DEM-CB100QXS-4XS	40G QSFP+ to 4* 10G SFP+ 1m Direct attach cable