


# 4G Cat 7 AX1500 Gigabit Router

D-Link's G413X 4G CAT 7 AX1500 Gigabit LTE Router allows you to access mobile broadband networks from anywhere and easily share it via Wi-Fi and fixed LAN ports. Once connected, you can check e-mail, surf the web, and stream media.

G413X

- Built-in Wi-Fi AX1500 distributes high-speed, high-performance Wi-Fi to all your connected devices
- Dual-band Wi-Fi with MU-MIMO technology makes 4K streaming, VR gaming or video chatting a breeze
- 3 Gigabit Ethernet LAN ports provides wired connectivity
- 1 Gigabit WAN port to connect to the internet
- Built-in SIM card slot supports 4G/LTE CAT 7
- Supports PPTP, L2TP, IPSec Passthrough
- WPA3 / WPA2 / WPA2 Mixed / WPA2+WPA3 Mixed / WEP



300 Mbps / 100 Mbps

## High-speed 4G CAT 7 Internet

Connect with 4G CAT 7 speeds of up to 300 Mbps for experience lightning-fast downloads



## Dual-Band AX1500

AX1500 provides plenty of bandwidth for video streaming, cloud storage & social media



## Gigabit Ethernet Ports

High-speed connections for wired devices and wired broadband.



## Up to 64 Devices

Connect all of your home's Wi-Fi devices to share a single broadband connection.



## SIM Slot

Simply insert your SIM card to share your mobile broadband connection throughout the home.



## Supports IPv6

Future-proof and compatible with the next generation of Internet standards.

Technical Specifications		
General		
Device Interface	3 x Gigabit LAN Port 1 x Gigabit WAN port 1 x SIM Slot	
Buttons	Power Button, Reset/WPS Button	
LED	Power / Internet / ETH / 2.4G / 5.8G / 4x LTE Strength	
Antenna Type	2 x 5dBi 2.4G & 5G external antenna 2 x 5dBi LTE external antenna	
Wi-Fi Data Rate	2.4GHz up to 300Mbps 5GHz up to 1200Mbps	
Wireless IEEE Standard	IEEE 802.11 ax/ac/n/g/b	
Other Protocols	TCP/IP, IPV6, DHCP, RADVD, DHCPv6, ICMP, NAT, PPPoE, PPPoEv6	
Bandwidth		
4G FDD	B1/B3/B5/B7/B8/B20/B28/B32 can be customized	
4G TDD	B38/B40/B41	
2CA Band combination (optional)	B1 + B1/B3/B5/B7/B8/B20/B28/B40/B41 B5 + B7/B40/B41 B7 + B7/B8/B20/B28 B8 + B40/B41	B3 + B3/B5/B7/B8/B20/B28/B38/B40/B41 B20 + B32/B38 B28 + B40/B41
WCDMA	B1/B5/B8	
Functionality		
Security Protocol	WEP, WPA2, WPA2 Mixed, WPA3, WPA2+WPA3 Mixed	
Firewall	NAT firewall, SPI firewall, DOS, ALG, IP Filtering, MAC Filtering, URL Filtering	
Features	QAM-1024, OFDMA, MU-MIMO, BSS coloring	
Mesh	D-Link EasyMesh	
TR069	support data model TR098, TR181, TR143, STUN)	
Physical		
Size	164 x 101 x 187mm	
Weight	232.7g	
Power input	DC 12V/1A ± 5%	
Operating Temperature	0°C~40°C	
Storage Temperature	-40°C~70°C	
Operating Humidity	10~90% (non-condensing)	
Storage Humidity	5~95% (non-condensing)	
Certification		
Regulation Compliance	CE	
Order Information		
Part Number	Description	
G413X	4G Cat 7 AX1500 Gigabit Router	