

### AirPremier Wireless G Outdoor AP/Bridge

#### For Business-Class Environments

- + Up to 54Mbps Wireless Speed in 2.4GHz Frequency Band<sup>2</sup>
- + Dual 5dBi High-Gain Antennas
- + AP Grouping for Bandwidth Enhancement

#### Multiple Operation Modes

- + Access Point
- + WDS With AP
- + WDS

#### Advanced Security

- + 64/128/152-Bit WEP Data Encryption
- + WPA/WPA2 Personal
- + WPA/WPA2 Enterprise
- + WPA-PSK/AES Over WDS
- + MAC Address Filtering
- + Multiple SSID Network Segmentation
- + 802.1Q VLAN Tagging Support
- + Load Balancing
- + Redundancy
- + System Log

#### Outdoor Installation

- + Power over Ethernet Support<sup>1</sup>
- + Diecast Watertight Housing
- + Built-in Heater With Sensor
- + Power Surge Arrestor Included
- + Mounting Kit for Wall and Wall Mounting

#### Versatile Management

- + Windows-Based AP Manager Utility
- + Web-Based Management
- + Telnet
- + MIB for SNMP Management

<sup>1</sup> Power consumption may exceed 802.3af PoE standard when heater is in operation; connect this device through the included PoE Base Unit.

<sup>2</sup> Maximum wireless signal rate based on IEEE 802.11g specifications. Actual data throughput will vary. Network conditions and environmental factors, including volume of network traffic, building materials and construction, and network overhead may lower actual data throughput rate.

The DWL-2700AP wireless G outdoor access point is an outdoor device with dual high Gain antennas that covers a large operating distance. This device is ideal for Internet Service Providers to create hot spot networks to provide outdoor users with wireless Internet access. It can also be installed at manufacturing plants, industrial locations, convention halls, school campuses, airports, golf courses, marinas and other outdoor venues.

#### Powerful & Durable Outdoor Solution.

The DWL-2700AP is designed to handle a wide variety of outdoor environments. It has a die-cast watertight housing, a built-in heater and a temperature sensor. Supporting 802.3af Power over Ethernet (PoE), it can be placed at outdoor locations where power outlets are not easily accessible. <sup>1</sup> Besides functioning as an AP, this device can be configured to operate as a Wireless Distribution System (WDS) to act as a bridge linking together networks in different buildings.

#### Advanced Network Security.

The DWL-2700AP supports 64/128/152-bit WEP data encryption and WPA/WPA2 security functions. In addition, it provides MAC Address Filtering to control user access, and the Disable SSID Broadcast function to limit outsiders' access to the internal network.

#### Network Flexibility and Efficiency.

The DWL-2700AP supports up to 8 SSID, allowing the administrators to logically divide the access point into several virtual access points all within a single hardware platform. Rather than having two separate networks with two access points, administrators can deploy one single AP to support more than one application, such as public Internet access and internal network control to increase flexibility and keep costs down. The DWL-2700AP supports 802.1Q VLAN Tagging, operating with multiple SSID to segment traffic to enhance performance and security.

The DWL-2700AP provides WLAN STA partitioning, a function useful for deployments like at hot spots. With station-to-station partitioning enabled, security is enhanced, since wireless users cannot peek at each other, and the possibility for data thievery is reduced. Administrators can, however, disable this function, so wireless users at an office can share hard disks and information, and peripherals such as wireless printers. The DWL-2700AP also supports AP grouping, allowing several access points to balance wireless network traffic and wireless clients among the AP with the same SSID and different non-overlapping frequency channels.



#### Network Management.

Network administrators can manage DWL-2700AP's settings via web-based configuration or Telnet. Administrators can use a Windows-based utility called AP Manager to automatically discover all wireless devices installed on the network and do bulk configuration of multiple AP to save time and effort.



### AirPremier Wireless G Outdoor AP/Bridge

#### Technical Specifications

Standards	<ul style="list-style-type: none"> <li>+ IEEE 802.11b/g WLAN</li> <li>+ IEEE 802.3/802.3u Ethernet</li> <li>+ IEEE 802.3x Flow Control</li> </ul>
Ethernet Interface	+ 10/100BASE-TX Ethernet port
Radio and Modulation Type	<p>For 802.11b:</p> <p>DSSS:</p> <ul style="list-style-type: none"> <li>+ DBPSK @ 1Mbps</li> <li>+ DQPSK @ 2Mbps</li> <li>+ CCK @ 5.5 and 11Mbps</li> </ul> <p>For 802.11g:</p> <p>OFDM:</p> <ul style="list-style-type: none"> <li>+ BPSK @ 6 and 9Mbps</li> <li>+ QPSK @ 12 and 18Mbps</li> <li>+ 16QAM @ 24 and 36Mbps</li> <li>+ 64QAM @ 48 and 54Mbps</li> </ul> <p>DSSS:</p> <ul style="list-style-type: none"> <li>+ DBPSK @ 1Mbps</li> <li>+ DQPSK @ 2Mbps</li> <li>+ CCK @ 5.5 and 11Mbps</li> </ul>
Operating Frequency	+ 2400 to 2483.5MHz
Channel Numbers	<ul style="list-style-type: none"> <li>+ 11 Channels (FCC)</li> <li>+ 13 Channels (ETSI)</li> </ul>
Data Rates	<ul style="list-style-type: none"> <li>+ 802.11g: 54, 48, 36, 24, 18, 12, 9 and 6Mbps</li> <li>+ 802.11b: 11, 5.5, 2, and 1Mbps</li> </ul>
Maximum Transmit Output Power <sup>3</sup>	23dBm (typical)
Antennas	Dual 5dBi Gain Reverse-N Type dipole antennas
Wireless Operating Range <sup>4</sup>	<p>802.11g (Full Power with 5dBi gain diversity dipole antennas):</p> <p>Indoor:</p> <ul style="list-style-type: none"> <li>+ 30 m (98 ft) @ 54Mbps      + 34 m (112 ft) @ 48Mbps</li> <li>+ 56 m (184 ft) @ 18Mbps      + 66 m (217 ft) @ 12Mbps</li> <li>+ 79 m (259 ft) @ 9Mbps      + 99 m (325 ft) @ 6Mbps</li> </ul> <p>Outdoor:</p> <ul style="list-style-type: none"> <li>+ 112 m (367 ft) @ 54Mbps      + 250 m (820 ft) @ 18Mbps</li> <li>+ 500 m (1,640 ft) @ 6Mbps</li> </ul>
Security	<ul style="list-style-type: none"> <li>+ 64/128/152-bit WEP data encryption</li> <li>+ WPA-PSK, WPA2-PSK</li> <li>+ WPA-EAP, WPA2-EAP</li> <li>+ TKIP, AES support</li> <li>+ MAC address filtering user access</li> <li>+ WLAN STA partitioning</li> <li>+ Multiple SSID for network segmentation</li> <li>+ SSID broadcast disable function</li> <li>+ 802.1Q VLAN Tagging</li> </ul>
Configurable Modes	<ul style="list-style-type: none"> <li>+ Access Point</li> <li>+ WDS With AP</li> <li>+ WDS</li> </ul>
Performance Enhancement	+ AP grouping for load balance



### AirPremier Wireless G Outdoor AP/Bridge

Device Management	Web Browser Interface: + HTTP + Secure HTTP (HTTPS) AP Manager SNMP support: + D-View module + Private MIB Command Line Interface: + Telnet + Secure (SSH) Telnet
Diagnostic LEDs	+ Power LED                      + 10/100Mbps                      + 802.11b/g
Accessories Provided for Outdoor Installation	+ 2 surge arrestors + PoE base unit + RF jumper cable (1 meter long) + Ethernet cable (30 meters long) + Set of grounding wires + 2 mounting kits
Operating Voltage	48VDC +/- 10% for PoE
Power Consumption	+ 8.5 watts (max.) with PoE (with heater OFF) + 28.5 watts (max.) with PoE (with heater ON) <sup>1</sup>
Dimensions	+ 277.7 (L) x 155 (W) x 45 (H) mm (10.93 x 6.10 x 1.77 inches)
Weight	+ 1.82 kg (4.1 lbs)
Operating Temperature	+ -40° to 60° C (-40° to 140° F)
Storage Temperature	+ -40° to 65° C (-40° to 149° F)
Operating Humidity	+ 5% to 95% non-condensing, all-weather enclosure
Regulation Certification	+ FCC Class B + CE + IP 68 + C-Tick

<sup>1</sup> Power consumption may exceed 802.3af PoE standard when heater is in operation; connect this device through the included PoE Base Unit.

<sup>2</sup> Maximum wireless signal rate based on IEEE 802.11g specifications. Actual data throughput will vary. Network conditions and environmental factors, including volume of network traffic, building materials and construction, and network overhead may lower actual data throughput rate.

<sup>3</sup> Maximum power setting will vary according to individual country regulations.

<sup>4</sup> Environmental factors may adversely affect operation range.



### D-Link Worldwide Offices

<b>U.S.A.</b>	TEL: 1-800-326-1688	FAX: 1-866-743-4905	<b>Italy</b>	TEL: 39-02-2900-0676	FAX: 39-02-2900-1723	<b>Egypt</b>	TEL: 202-291-9047	FAX: 202-291-9051
<b>Canada</b>	TEL: 1-905-8295033	FAX: 1-905-8295223	<b>Spain</b>	TEL: 34-93-409 0770	FAX: 34-93-491 0795	<b>Turkey</b>	TEL: 90-212-289-5659	FAX: 90-212-289-7606
<b>Europe (U. K.)</b>	TEL: 44-20-8955-9000	FAX: 44-20-8955-9001	<b>Portugal</b>	TEL: 351-21-8688493	FAX: 351-21-8622492	<b>Iran</b>	TEL: 98-21-888-22613	FAX: 98-21-888-35492
<b>Germany</b>	TEL: 49-6196-77990	FAX: 49-6196-7799300	<b>Greece</b>	TEL: 30-210-9914 512	FAX: 30-210-9916 902	<b>Pakistan</b>	TEL: 92-21-454-8158	FAX: 92-21-453-5103
<b>France</b>	TEL: 33-1-30238688	FAX: 33-1-30238689	<b>Czech Republic</b>	TEL: 420 224 247 500	FAX: 420 224 234 967	<b>Israel</b>	TEL: 972-9-9715700	FAX: 972-9-9715601
<b>Netherlands</b>	TEL: 31-10-282-1445	FAX: 31-10-282-1331	<b>Hungary</b>	TEL: 36-(0)-1-461-30-00	FAX: 36-(0)-1-461-30-04	<b>LatinAmerica</b>	TEL: 56-2-5838-950	FAX: 56-2-5838-953
<b>Belgium &amp; Luxembourg</b>	TEL: 32(0)2-517-7111	FAX: 32(0)2-517-6500	<b>Poland</b>	TEL: 48-(0)-22-583-92-75	FAX: 48-(0)-22-583-92-76	<b>Brazil</b>	TEL: 55-11-2185-9300	FAX: 55-11-2185-9322
<b>Switzerland</b>	TEL: 41 (0) 1 832 11 00	FAX: 41 (0) 1 832 11 01	<b>Bulgaria</b>	TEL: 359 2 958 22 42	FAX: 359 2 958 65 57	<b>South Africa</b>	TEL: 27-12-665-2165	FAX: 27-12-665-2186
<b>Austria</b>	TEL: 43 (0) 1 240 27 270	FAX: 43 (0) 1 240 27 271	<b>Romania</b>	TEL: 40(0)21 320 23 05	FAX: 40(0)21 320 23 07	<b>Russia</b>	TEL: 7-495-744-0099	FAX: 7-495-744-0099 #350
<b>Sweden</b>	TEL: 46-(0)8 564-61900	FAX: 46-(0)8 564-61901	<b>Singapore</b>	TEL: 65-6774-6233	FAX: 65-6774-6322	<b>Japan</b>	TEL: 81-3-5781-0963	FAX: 81-3-5781-0965
<b>Denmark</b>	TEL: 45-43-969040	FAX: 45-43-424347	<b>Australia</b>	TEL: 61-2-8899-1800	FAX: 61-2-8899-1868	<b>Korea</b>	TEL: 82-2-890-5491	FAX: 82-2-890-549
<b>Norway</b>	TEL: 47 99 300 100	FAX: 47 22 30 95 80	<b>India</b>	TEL: 91-22-2652 6696	FAX: 91-22-2652 8914	<b>China</b>	TEL: 86-10-58635800	FAX: 86-10-58635799
<b>Finland</b>	TEL: 358-10 309 8840	FAX: 358-10 309 8841	<b>Middle East (Dubai)</b>	TEL: 971-4-3916480	FAX: 971-4-3908881	<b>Taiwan</b>	TEL: 886-2-6600-0123	FAX: 886-2-6600-3939
						<b>Headquarters</b>	TEL: 886-2-6600-0123	FAX: 886-2-6600-9898